

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA
Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repil.it - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

SCHEDA TECNICA TECHNICAL DATA SHEET

**PRODOTTO:
PRODUCT:**

YELLOW REPIPLAST/PU '22223'

Descrizione / Description

Dispersion of pigments in plasticizer

Funzione / Use

Colour for plastic materials.

Idoneo per / Suitable for

LDPE	ABS	PET	TR		UP
HDPE	PSA	PA	TPU		POM
PP	PSC	PMMA	PU ester	x	
PVC	SAN	PC	PU ether	x	

Caratteristiche / Features

Metodo / Method

Aspetto Appearance	LIQUID	Visual
Colore Colour	YELLOW	Visual
Viscosità a 20°C (cP) Viscosity at 20°C (cP)	7000	MO-LT-03(*)
Peso Specifico a 20°C (g/ml) Specific Gravity at 20°C (g/ml)	0,95	MO-LT-019(**)

(*) Brookfield RVF, disco N.5,20 giri minuto a 20°C, valore indicativo.
Brookfield RVF, spindle N.5,20 rpm at 20°C, indicative value.

(**) Valore indicativo.
Indicative value.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA

Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repil.it - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

PRODOTTO:**PRODUCT:****YELLOW REPIPLAST/PU '22223'****Indicazioni di impiego / General recommendations**

Use the product at the addition rate suggested by Repi.

Manipolazione e Stoccaggio / Handling and Storage

We recommend that you stir the product before using it. We suggest that the product be stored at room temperature. The viscosity of the product may greatly increase if it is stored at a low temperature. If this occurs, bring the product to room temperature and mix well prior to using it.

To avoid any humidity absorption and potential pollution, please store the product in a tightly sealed container.

Storage life: 6 months in sealed containers

Misure di sicurezza / Safety measures

Please refer to the information included on the material safety data sheet.

Redatta il/Completed on 1/06/98

Emissione nr/Issue nr 1

Repi S.p.A.
Via B. Franklin, 2
21050 LONATE CEPPINO (VA) - ITALY
Tel. +39 0331 819511 - Fax +39 0331 819581
E-mail repi@repil.it www.repi.it

REPI, LLC.
8700 Red Oak Boulevard, Suite D
Charlotte, North Carolina 28217
Tel. +1 704 5228841 - Fax +1 704 5228788
E-mail info@repil-usa.com www.repi-usa.com

All information given in this technical sheet are in accordance to our best knowledge and can in no way be considered as an absolute guarantee on the final result which is linked to the specific working process of the customer.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA
Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repit - www.repit

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

SCHEDA TECNICA TECHNICAL DATA SHEET

**PRODOTTO:
PRODUCT:**

BLUE REPIPLAST/PU '66614'

Descrizione / Description

Dispersion of pigments in plasticizer

Funzione / Use

Colour for plastic materials.

Idoneo per / Suitable for

LDPE	ABS	PET	TR	UP
HDPE	PSA	PA	TPU	POM
PP	PSC	PMMA	PU ester	x
PVC x	SAN	PC	PU ether	x

Caratteristiche / Features

Metodo / Method

Aspetto Appearance	LIQUID	Visual
Colore Colour	BLUE	Visual
Viscosità a 20°C (cP) Viscosity at 20°C (cP)	2500	MO-LT-03(*)
Peso Specifico a 20°C (g/ml) Specific Gravity at 20°C (g/ml)	0,95	MO-LT-019(**)

(*) Brookfield RVF, disco N.4,20 giri minuto a 20°C, valore indicativo.
Brookfield RVF, spindle N.4,20 rpm at 20°C, indicative value.

(**) Valore indicativo.
Indicative value.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA

Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repil.it - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

PRODOTTO:**PRODUCT:****BLUE REPIPLAST/PU '66614'****Indicazioni di impiego / General recommendations**

Use the product at the addition rate suggested by Repi.

Manipolazione e Stoccaggio / Handling and Storage

We recommend that you stir the product before using it. We suggest that the product be stored at room temperature. The viscosity of the product may greatly increase if it is stored at a low temperature. If this occurs, bring the product to room temperature and mix well prior to using it.

To avoid any humidity absorption and potential pollution, please store the product in a tightly sealed container.

Storage life: 6 months in sealed containers

Misure di sicurezza / Safety measures

Please refer to the information included on the material safety data sheet.

Redatta il/Completed on 1/06/98

Emissione nr/Issue nr 1

Repi S.p.A.
Via B. Franklin, 2
21050 LONATE CEPPINO (VA) - ITALY
Tel. +39 0331 819511 - Fax +39 0331 819581
E-mail repi@repil.it www.repi.it

REPI, LLC.
8700 Red Oak Boulevard, Suite D
Charlotte, North Carolina 28217
Tel. +1 704 5228841 - Fax +1 704 5228788
E-mail info@repil-usa.com www.repi-usa.com

All information given in this technical sheet are in accordance to our best knowledge and can in no way be considered as an absolute guarantee on the final result which is linked to the specific working process of the customer.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA
Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repil.it - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

SCHEDA TECNICA TECHNICAL DATA SHEET

**PRODOTTO:
PRODUCT:**

ORANGE REPIPLAST/PU '33306'

Descrizione / Description

Dispersion of pigments in plasticizer

Funzione / Use

Colour for plastic materials.

Idoneo per / Suitable for

LDPE	ABS	PET	TR		UP
HDPE	PSA	PA	TPU		POM
PP	PSC	PMMA	PU ester	x	
PVC	SAN	PC	PU ether	x	

Caratteristiche / Features

Metodo / Method

Aspetto Appearance	PASTE	Visual
Colore Colour	ORANGE	Visual
Viscosità a 20°C (cP) Viscosity at 20°C (cP)	1400	MO-LT-03(*)
Peso Specifico a 20°C (g/ml) Specific Gravity at 20°C (g/ml)	1,00	MO-LT-019(**)

(*) Brookfield RVF, disco N.4,20 giri minuto a 20°C, valore indicativo.
Brookfield RVF, spindle N.4,20 rpm at 20°C, indicative value.

(**) Valore indicativo.
Indicative value.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA
Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repil.it - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

PRODOTTO:**PRODUCT:****ORANGE REPIPLAST/PU '33306'****Indicazioni di impiego / General recommendations**

Use the product at the addition rate suggested by Repi.

Manipolazione e Stoccaggio / Handling and Storage

To avoid any humidity absorption and potential pollution, please store the product in a tightly sealed container.

Storage life: 6 months in sealed containers

Misure di sicurezza / Safety measures

Please refer to the information included on the material safety data sheet.

Redatta il/Completed on 1/06/98

Emissione nr/Issue nr 1

Repi S.p.A.
Via B. Franklin, 2
21050 LONATE CEPPINO (VA) - ITALY
Tel. +39 0331 819511 - Fax +39 0331 819581
E-mail repi@repil.it www.repi.it

REPI, LLC.
8700 Red Oak Boulevard, Suite D
Charlotte, North Carolina 28217
Tel. +1 704 5228841 - Fax +1 704 5228788
E-mail info@repil-usa.com www.repi-usa.com

All information given in this technical sheet are in accordance to our best knowledge and can in no way be considered as an absolute guarantee on the final result which is linked to the specific working process of the customer.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA
Tel +39 0331 819511 - Fax +39 0331 819581 - repi.italia@repil.com - www.repi.com

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

SCHEDA TECNICA TECHNICAL DATA SHEET

**PRODOTTO:
PRODUCT:**

146 - REPI COLOUR

Descrizione / Description

Dispersion of pigments in polyether polyol

Funzione / Use

Colour for plastic materials.

Idoneo per / Suitable for

LDPE	ABS	PET	TR	UP
HDPE	PSA	PA	TPU	POM
PP	PSC	PMMA	PU ester	
PVC	SAN	PC	PU ether	x

Caratteristiche / Features

Metodo / Method

Aspetto Appearance	LIQUID	Visual
Colore Colour	GREY	Visual
Viscosità a 20°C (cP) Viscosity at 20°C (cP)	8000	MO-LT-03(*)
Peso Specifico a 20°C (g/ml) Specific Gravity at 20°C (g/ml)	1,40	MO-LT-019(**)
Numero Ossidrilie (mg KOH/g) Hydroxyl Value (mg KOH/g)	019	Calculated

(*) Brookfield RVF, disco N.5,20 giri minuto a 20°C, valore indicativo.
Brookfield RVF, spindle N.5,20 rpm at 20°C, indicative value.

(**) Valore indicativo.
Indicative value.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA
Tel +39 0331 819511 - Fax +39 0331 819581 - repi.italia@repil.com - www.repi.com

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

PRODOTTO:**PRODUCT:****146 - REPI COLOUR****Indicazioni di impiego / General recommendations**

Use the product at the addition rate suggested by Repi.

Manipolazione e Stoccaggio / Handling and Storage

We recommend that you stir the product before using it. We suggest that the product be stored at room temperature. The viscosity of the product may greatly increase if it is stored at a low temperature. If this occurs, bring the product to room temperature and mix well prior to using it.

To avoid any humidity absorption and potential pollution, please store the product in a tightly sealed container.

Storage life: 6 months in sealed containers.

Misure di sicurezza / Safety measures

Please refer to the information included on the material safety data sheet.

Redatta il/Completed on 16/06/04

Emissione nr/Issue nr 1

Repi S.p.A.
Via B. Franklin, 2
21050 LONATE CEPPINO (VA) - ITALY
Tel. +39 0331 819511 - Fax +39 0331 819581
repil.italia@repil.com www.repi.com

REPI, LLC.
2825 Repi Court
Dallas, North Carolina 28034
Tel. +1 704 648-0252 - Fax +1 704 648-0261
repil.usa@repil.com www.repi.com

All information given in this technical sheet are in accordance to our best knowledge and can in no way be considered as an absolute guarantee on the final result which is linked to the specific working process of the customer.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA
Tel +39 0331 819511 - Fax +39 0331 819581 - repi.italia@repil.com - www.repi.com

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

SCHEDA TECNICA TECHNICAL DATA SHEET

**PRODOTTO:
PRODUCT:**

GREY REPIPLAST 90739

Descrizione / Description

Dispersion of pigments in not-phthalic plasticizer

Funzione / Use

Colour for plastic materials.

Idoneo per / Suitable for

LDPE	ABS	PET	TR		UP
HDPE	PSA	PA	TPU		POM
PP	PSC	PMMA	PU ester	x	
PVC	SAN	PC	PU ether	x	

Caratteristiche / Features

Metodo / Method

Colore
Colour

GREY

Visual

Viscosità a 20°C (cP)
Viscosity at 20°C (cP)

5000

MO-LT-03(*)

Peso Specifico a 20°C (g/ml)
Specific Gravity at 20°C (g/ml)

1,20

MO-LT-019(**)

(*) Brookfield RVF, disco N.4,20 giri minuto a 20°C, valore indicativo.
Brookfield RVF, spindle N.4,20 rpm at 20°C, indicative value.

(**) Valore indicativo.
Indicative value.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA
Tel +39 0331 819511 - Fax +39 0331 819581 - repi.italia@repil.com - www.repi.com

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

PRODOTTO:**PRODUCT:****GREY REPIPLAST 90739****Indicazioni di impiego / General recommendations**

Use the product at the addition rate suggested by Repi.

Manipolazione e Stoccaggio / Handling and Storage

To avoid any humidity absorption and potential pollution, please store the product in a tightly sealed container.

Storage life: 6 months in sealed containers.

Misure di sicurezza / Safety measures

Please refer to the information included on the material safety data sheet.

Redatta il/Completed on 8/05/12

Emissione nr/Issue nr 1

Repi S.p.A.
Via B. Franklin, 2
21050 LONATE CEPPINO (VA) - ITALY
Tel. +39 0331 819511 - Fax +39 0331 819581
repil.italia@repil.com www.repi.com

REPI, LLC.
2825 Repi Court
Dallas, North Carolina 28034
Tel. +1 704 648-0252 - Fax +1 704 648-0261
repil.usa@repil.com www.repi.com

All information given in this technical sheet are in accordance to our best knowledge and can in no way be considered as an absolute guarantee on the final result which is linked to the specific working process of the customer.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA
Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repil.it - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

SCHEDA TECNICA TECHNICAL DATA SHEET

**PRODOTTO:
PRODUCT:**

BLACK REPIPLAST 99807FL

Descrizione / Description

Carbon black dispersion in plasticizer

Funzione / Use

Colour for plastic materials.

Idoneo per / Suitable for

LDPE	ABS	PET	TR		UP
HDPE	PSA	PA	TPU		POM
PP	PSC	PMMA	PU ester	x	
PVC	SAN	PC	PU ether	x	

Caratteristiche / Features

Metodo / Method

Aspetto Appearance	LIQUID	Visual
Colore Colour	BLACK	Visual
Viscosità a 20°C (cP) Viscosity at 20°C (cP)	1500	MO-LT-03(*)
Peso Specifico a 20°C (g/ml) Specific Gravity at 20°C (g/ml)	1,10	MO-LT-019(**)

(*) Brookfield RVF, disco N.5,20 giri minuto a 20°C, valore indicativo.
Brookfield RVF, spindle N.5,20 rpm at 20°C, indicative value.

(**) Valore indicativo.
Indicative value.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA

Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repil.it - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

PRODOTTO:**PRODUCT:****BLACK REPIPLAST 99807FL****Indicazioni di impiego / General recommendations**

Use the product at the addition rate suggested by Repi. |

Manipolazione e Stoccaggio / Handling and Storage

We recommend that you stir the product before using it. We suggest that the product be stored at room temperature. The viscosity of the product may greatly increase if it is stored at a low temperature. If this occurs, bring the product to room temperature and mix well prior to using it.

To avoid any humidity absorption and potential pollution, please store the product in a tightly sealed container.

Storage life: 6 months in sealed containers

Misure di sicurezza / Safety measures

Please refer to the information included on the material safety data sheet.

Redatta il/Completed on 4/07/07

Emissione nr/Issue nr 1

Repi S.p.A.
Via B. Franklin, 2
21050 LONATE CEPPINO (VA) - ITALY
Tel. +39 0331 819511 - Fax +39 0331 819581
E-mail repi@repil.it www.repi.it

REPI, LLC.
8700 Red Oak Boulevard, Suite D
Charlotte, North Carolina 28217
Tel. +1 704 5228841 - Fax +1 704 5228788
E-mail info@repil-usa.com www.repi-usa.com

All information given in this technical sheet are in accordance to our best knowledge and can in no way be considered as an absolute guarantee on the final result which is linked to the specific working process of the customer.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA
Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repil.it - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

SCHEDA TECNICA TECHNICAL DATA SHEET

**PRODOTTO:
PRODUCT:**

136 - REPI COLOUR

Descrizione / Description

Dispersion of pigments in plasticizer

Funzione / Use

Colour for plastic materials.

Idoneo per / Suitable for

LDPE	ABS	PET	TR		UP
HDPE	PSA	PA	TPU		POM
PP	PSC	PMMA	PU ester	x	
PVC	SAN	PC	PU ether	x	

Caratteristiche / Features

Metodo / Method

Aspetto Appearance	LIQUID	Visual
Colore Colour	BEIGE	Visual
Viscosità a 20°C (cP) Viscosity at 20°C (cP)	6000	MO-LT-03(*)
Peso Specifico a 20°C (g/ml) Specific Gravity at 20°C (g/ml)	1,60	MO-LT-019(**)

(*) Brookfield RVF, disco N.4,20 giri minuto a 20°C, valore indicativo.
Brookfield RVF, spindle N.4,20 rpm at 20°C, indicative value.

(**) Valore indicativo.
Indicative value.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA

Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repil.it - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

PRODOTTO:**PRODUCT:****136 - REPI COLOUR****Indicazioni di impiego / General recommendations**

Use the product at the addition rate suggested by Repi.

Manipolazione e Stoccaggio / Handling and Storage

We recommend that you stir the product before using it. We suggest that the product be stored at room temperature. The viscosity of the product may greatly increase if it is stored at a low temperature. If this occurs, bring the product to room temperature and mix well prior to using it.

To avoid any humidity absorption and potential pollution, please store the product in a tightly sealed container.

Storage life: 6 months in sealed containers

Misure di sicurezza / Safety measures

Please refer to the information included on the material safety data sheet.

Redatta il/Completed on 23/08/11

Emissione nr/Issue nr 1

Repi S.p.A.
Via B. Franklin, 2
21050 LONATE CEPPINO (VA) - ITALY
Tel. +39 0331 819511 - Fax +39 0331 819581
E-mail repi@repil.it www.repi.it

REPI, LLC.
8700 Red Oak Boulevard, Suite D
Charlotte, North Carolina 28217
Tel. +1 704 5228841 - Fax +1 704 5228788
E-mail info@repil-usa.com www.repi-usa.com

All information given in this technical sheet are in accordance to our best knowledge and can in no way be considered as an absolute guarantee on the final result which is linked to the specific working process of the customer.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA
Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repit - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

SCHEDA TECNICA TECHNICAL DATA SHEET

**PRODOTTO:
PRODUCT:**

132 - REPI COLOUR

Descrizione / Description

Carbon black dispersion in polyether polyol

Funzione / Use

Colour for plastic materials.

Idoneo per / Suitable for

LDPE	ABS	PET	TR	UP
HDPE	PSA	PA	TPU	POM
PP	PSC	PMMA	PU ester	
PVC	SAN	PC	PU ether	x

Caratteristiche / Features

Metodo / Method

Aspetto Appearance	LIQUID	Visual
Colore Colour	BLACK	Visual
Viscosità a 20°C (cP) Viscosity at 20°C (cP)	4000	MO-LT-03(*)
Peso Specifico a 20°C (g/ml) Specific Gravity at 20°C (g/ml)	1,15	MO-LT-019(**)
Numero Ossidrilie (mg KOH/g) Hydroxyl Value (mg KOH/g)	21	Calculated

(*) Brookfield RVF, disco N.4,20 giri minuto a 20°C, valore indicativo.
Brookfield RVF, spindle N.4,20 rpm at 20°C, indicative value.

(**) Valore indicativo.
Indicative value.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA

Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repil.it - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

PRODOTTO:**PRODUCT:****132 - REPI COLOUR****Indicazioni di impiego / General recommendations**

Use the product at the addition rate suggested by Repi.

Manipolazione e Stoccaggio / Handling and Storage

We recommend that you stir the product before using it. We suggest that the product be stored at room temperature. The viscosity of the product may greatly increase if it is stored at a low temperature. If this occurs, bring the product to room temperature and mix well prior to using it.

To avoid any humidity absorption and potential pollution, please store the product in a tightly sealed container.

Storage life: 6 months in sealed containers

Misure di sicurezza / Safety measures

Please refer to the information included on the material safety data sheet.

Redatta il/Completed on 1/12/04

Emissione nr/Issue nr 4

Repi S.p.A.
Via B. Franklin, 2
21050 LONATE CEPPINO (VA) - ITALY
Tel. +39 0331 819511 - Fax +39 0331 819581
E-mail repi@repil.it www.repi.it

REPI, LLC.
8700 Red Oak Boulevard, Suite D
Charlotte, North Carolina 28217
Tel. +1 704 5228841 - Fax +1 704 5228788
E-mail info@repil-usa.com www.repi-usa.com

All information given in this technical sheet are in accordance to our best knowledge and can in no way be considered as an absolute guarantee on the final result which is linked to the specific working process of the customer.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA
Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repit - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

SCHEDA TECNICA TECHNICAL DATA SHEET

**PRODOTTO:
PRODUCT:**

131- REPI COLOUR

Descrizione / Description

Dispersion of pigments in plasticizer

Funzione / Use

Colour for plastic materials.

Idoneo per / Suitable for

LDPE	ABS	PET	TR		UP
HDPE	PSA	PA	TPU		POM
PP	PSC	PMMA	PU ester	x	
PVC	SAN	PC	PU ether	x	

Caratteristiche / Features

Metodo / Method

Aspetto Appearance	LIQUID	Visual
Colore Colour	BEIGE	Visual
Viscosità a 20°C (cP) Viscosity at 20°C (cP)	1500	MO-LT-03(*)
Peso Specifico a 20°C (g/ml) Specific Gravity at 20°C (g/ml)	1,40	MO-LT-019(**)

(*) Brookfield RVF, disco N.4,20 giri minuto a 20°C, valore indicativo.
Brookfield RVF, spindle N.4,20 rpm at 20°C, indicative value.

(**) Valore indicativo.
Indicative value.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA

Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repil.it - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

PRODOTTO:**PRODUCT:****131- REPI COLOUR****Indicazioni di impiego / General recommendations**

Use the product at the addition rate suggested by Repi.

Manipolazione e Stoccaggio / Handling and Storage

We recommend that you stir the product before using it. We suggest that the product be stored at room temperature. The viscosity of the product may greatly increase if it is stored at a low temperature. If this occurs, bring the product to room temperature and mix well prior to using it.

To avoid any humidity absorption and potential pollution, please store the product in a tightly sealed container.

Storage life: 6 months in sealed containers

Misure di sicurezza / Safety measures

Please refer to the information included on the material safety data sheet.

Redatta il/Completed on 21/06/11

Emissione nr/Issue nr 1

Repi S.p.A.
Via B. Franklin, 2
21050 LONATE CEPPINO (VA) - ITALY
Tel. +39 0331 819511 - Fax +39 0331 819581
E-mail repi@repil.it www.repi.it

REPI, LLC.
8700 Red Oak Boulevard, Suite D
Charlotte, North Carolina 28217
Tel. +1 704 5228841 - Fax +1 704 5228788
E-mail info@repil-usa.com www.repi-usa.com

All information given in this technical sheet are in accordance to our best knowledge and can in no way be considered as an absolute guarantee on the final result which is linked to the specific working process of the customer.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA
Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repit - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

SCHEDA TECNICA TECHNICAL DATA SHEET

**PRODOTTO:
PRODUCT:**

BLACK REPIPLAST 99807FL

Descrizione / Description

Carbon black dispersion in plasticizer

Funzione / Use

Colour for plastic materials.

Idoneo per / Suitable for

LDPE	ABS	PET	TR		UP
HDPE	PSA	PA	TPU		POM
PP	PSC	PMMA	PU ester	x	
PVC	SAN	PC	PU ether	x	

Caratteristiche / Features

Metodo / Method

Aspetto Appearance	LIQUID	Visual
Colore Colour	BLACK	Visual
Viscosità a 20°C (cP) Viscosity at 20°C (cP)	1500	MO-LT-03(*)
Peso Specifico a 20°C (g/ml) Specific Gravity at 20°C (g/ml)	1,10	MO-LT-019(**)

(*) Brookfield RVF, disco N.5,20 giri minuto a 20°C, valore indicativo.
Brookfield RVF, spindle N.5,20 rpm at 20°C, indicative value.

(**) Valore indicativo.
Indicative value.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA

Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repil.it - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

PRODOTTO:**PRODUCT:****BLACK REPIPLAST 99807FL****Indicazioni di impiego / General recommendations**

Use the product at the addition rate suggested by Repi. |

Manipolazione e Stoccaggio / Handling and Storage

We recommend that you stir the product before using it. We suggest that the product be stored at room temperature. The viscosity of the product may greatly increase if it is stored at a low temperature. If this occurs, bring the product to room temperature and mix well prior to using it.

To avoid any humidity absorption and potential pollution, please store the product in a tightly sealed container.

Storage life: 6 months in sealed containers

Misure di sicurezza / Safety measures

Please refer to the information included on the material safety data sheet.

Redatta il/Completed on 4/07/07

Emissione nr/Issue nr 1

Repi S.p.A.
Via B. Franklin, 2
21050 LONATE CEPPINO (VA) - ITALY
Tel. +39 0331 819511 - Fax +39 0331 819581
E-mail repi@repil.it www.repi.it

REPI, LLC.
8700 Red Oak Boulevard, Suite D
Charlotte, North Carolina 28217
Tel. +1 704 5228841 - Fax +1 704 5228788
E-mail info@repil-usa.com www.repi-usa.com

All information given in this technical sheet are in accordance to our best knowledge and can in no way be considered as an absolute guarantee on the final result which is linked to the specific working process of the customer.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA
Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repil.it - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

SCHEDA TECNICA TECHNICAL DATA SHEET

**PRODOTTO:
PRODUCT:**

124 - REPI COLOUR

Descrizione / Description

Dispersion of pigments in plasticizer

Funzione / Use

Colour for plastic materials.

Idoneo per / Suitable for

LDPE	ABS	PET	TR		UP
HDPE	PSA	PA	TPU		POM
PP	PSC	PMMA	PU ester	x	
PVC x	SAN	PC	PU ether	x	

Caratteristiche / Features

Metodo / Method

Aspetto Appearance	LIQUID	Visual
Colore Colour	RED	Visual
Viscosità a 20°C (cP) Viscosity at 20°C (cP)	1500	MO-LT-03(*)
Peso Specifico a 20°C (g/ml) Specific Gravity at 20°C (g/ml)	1,00	MO-LT-019(**)

(*) Brookfield RVF, disco N.4,20 giri minuto a 20°C, valore indicativo.
Brookfield RVF, spindle N.4,20 rpm at 20°C, indicative value.

(**) Valore indicativo.
Indicative value.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA

Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repil.it - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

PRODOTTO:**PRODUCT:****124 - REPI COLOUR****Indicazioni di impiego / General recommendations**

Use the product at the addition rate suggested by Repi.

Manipolazione e Stoccaggio / Handling and Storage

We recommend that you stir the product before using it. We suggest that the product be stored at room temperature. The viscosity of the product may greatly increase if it is stored at a low temperature. If this occurs, bring the product to room temperature and mix well prior to using it.

To avoid any humidity absorption and potential pollution, please store the product in a tightly sealed container.

Storage life: 6 months in sealed containers

Misure di sicurezza / Safety measures

Please refer to the information included on the material safety data sheet.

Redatta il/Completed on 1/06/98

Emissione nr/Issue nr 1

Repi S.p.A.
Via B. Franklin, 2
21050 LONATE CEPPINO (VA) - ITALY
Tel. +39 0331 819511 - Fax +39 0331 819581
E-mail repi@repil.it www.repi.it

REPI, LLC.
8700 Red Oak Boulevard, Suite D
Charlotte, North Carolina 28217
Tel. +1 704 5228841 - Fax +1 704 5228788
E-mail info@repil-usa.com www.repi-usa.com

All information given in this technical sheet are in accordance to our best knowledge and can in no way be considered as an absolute guarantee on the final result which is linked to the specific working process of the customer.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA
Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repil.it - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

SCHEDA TECNICA TECHNICAL DATA SHEET

**PRODOTTO:
PRODUCT:**

BLACK REPIPLAST/U 99288

Descrizione / Description

Carbon black dispersion in plasticizer

Funzione / Use

Colour for plastic materials.

Idoneo per / Suitable for

LDPE	ABS	PET	TR	UP
HDPE	PSA	PA	TPU	POM
PP	PSC	PMMA	PU ester	x
PVC x	SAN	PC	PU ether	x

Caratteristiche / Features

Metodo / Method

Aspetto Appearance	LIQUID	Visual
Colore Colour	BLACK	Visual
Viscosità a 20°C (cP) Viscosity at 20°C (cP)	1000	MO-LT-03(*)
Peso Specifico a 20°C (g/ml) Specific Gravity at 20°C (g/ml)	1,10	MO-LT-019(**)

(*) Brookfield RVF, disco N.4,20 giri minuto a 20°C, valore indicativo.
Brookfield RVF, spindle N.4,20 rpm at 20°C, indicative value.

(**) Valore indicativo.
Indicative value.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA

Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repil.it - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

PRODOTTO:**PRODUCT:****BLACK REPIPLAST/U 99288****Indicazioni di impiego / General recommendations**

Use the product at the addition rate suggested by Repi.

Manipolazione e Stoccaggio / Handling and Storage

We recommend that you stir the product before using it. We suggest that the product be stored at room temperature. The viscosity of the product may greatly increase if it is stored at a low temperature. If this occurs, bring the product to room temperature and mix well prior to using it.

To avoid any humidity absorption and potential pollution, please store the product in a tightly sealed container.

Storage life: 6 months in sealed containers

Misure di sicurezza / Safety measures

Please refer to the information included on the material safety data sheet.

Redatta il/Completed on 1/06/98

Emissione nr/Issue nr 1

Repi S.p.A.
Via B. Franklin, 2
21050 LONATE CEPPINO (VA) - ITALY
Tel. +39 0331 819511 - Fax +39 0331 819581
E-mail repi@repil.it www.repi.it

REPI, LLC.
8700 Red Oak Boulevard, Suite D
Charlotte, North Carolina 28217
Tel. +1 704 5228841 - Fax +1 704 5228788
E-mail info@repil-usa.com www.repi-usa.com

All information given in this technical sheet are in accordance to our best knowledge and can in no way be considered as an absolute guarantee on the final result which is linked to the specific working process of the customer.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA

Tel +39 0331 819511 - Fax +39 0331 819581 - repi.italia@repil.com - www.repi.com

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

TECHNICAL DATA SHEET

PRODUCT: BLANCO 19645 147-REPI COLOUR**Description**

Dispersion of pigments in plasticizer

Use

Colour for plastic materials.

Suitable for

PU ESTER

PU ETHER

PVC

Features		Method
Appearance	Liquid	Visual
Colour	WHITE	Visual (***)
Viscosity at 20°C	8.000 cP	MO-LT-03 (*)
Specific Gravity at 20°C	1,60 g/ml	MO-LT-019 (**)
(*) Brookfield RVF, spindle N. 5, 20 rpm at 20°C, indicative value.		
(**) Indicative value		
(***) The color as per visual inspection may not match the color of the final application.		
Decimal and Thousands Separators: in this document we follow the convention to use a period as thousands separator and a comma as decimal separator.		

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA

Tel +39 0331 819511 - Fax +39 0331 819581 - repi.italia@repil.com - www.repi.com

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

PRODUCT: BLANCO 19645 147-REPI COLOUR

General recommendations

Use the product at the addition rate suggested by Repi.

Handling and Storage

We recommend that you stir the product before using it.

The viscosity of the product may significantly increase if it is stored at low temperature.

If this occurs, bring the product to room temperature.

We suggest to store the product at room temperature.

To avoid any humidity absorption and potential pollution, please store the product in a tightly sealed container.

Storage life: 12 months in sealed containers.

Legislations Compliance

For details regarding the regulatory and compliance status, please ask to Regulatoryaffairs@repil.com. Please also check the food contact certificate document if available/applicable.

Safety measures

Please refer to the information included on the safety data sheet.

Issue no. 01 13.04.2006

All information given in this technical sheet are in accordance to our best knowledge and can in no way be considered as an absolute guarantee on the final result which is linked to the specific working process of the customer.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA
Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repil.it - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

SCHEDA TECNICA TECHNICAL DATA SHEET

**PRODOTTO:
PRODUCT:**

125 - REPI COLOUR

Descrizione / Description

Dispersion of pigments in plasticizer

Funzione / Use

Colour for plastic materials.

Idoneo per / Suitable for

LDPE	ABS	PET	TR		UP
HDPE	PSA	PA	TPU		POM
PP	PSC	PMMA	PU ester	x	
PVC x	SAN	PC	PU ether	x	

Caratteristiche / Features

Metodo / Method

Aspetto Appearance	LIQUID	Visual
Colore Colour	WHITE	Visual
Viscosità a 20°C (cP) Viscosity at 20°C (cP)	4500	MO-LT-03(*)
Peso Specifico a 20°C (g/ml) Specific Gravity at 20°C (g/ml)	1,50	MO-LT-019(**)

(*) Brookfield RVF, disco N.4,20 giri minuto a 20°C, valore indicativo.
Brookfield RVF, spindle N.4,20 rpm at 20°C, indicative value.

(**) Valore indicativo.
Indicative value.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA

Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repil.it - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

PRODOTTO:**PRODUCT:****125 - REPI COLOUR****Indicazioni di impiego / General recommendations**

Use the product at the addition rate suggested by Repi.

Manipolazione e Stoccaggio / Handling and Storage

We recommend that you stir the product before using it. We suggest that the product be stored at room temperature. The viscosity of the product may greatly increase if it is stored at a low temperature. If this occurs, bring the product to room temperature and mix well prior to using it.

To avoid any humidity absorption and potential pollution, please store the product in a tightly sealed container.

Storage life: 6 months in sealed containers

Misure di sicurezza / Safety measures

Please refer to the information included on the material safety data sheet.

Redatta il/Completed on 22/09/10

Emissione nr/Issue nr 1

Repi S.p.A.
Via B. Franklin, 2
21050 LONATE CEPPINO (VA) - ITALY
Tel. +39 0331 819511 - Fax +39 0331 819581
E-mail repi@repil.it www.repi.it

REPI, LLC.
8700 Red Oak Boulevard, Suite D
Charlotte, North Carolina 28217
Tel. +1 704 5228841 - Fax +1 704 5228788
E-mail info@repil-usa.com www.repi-usa.com

All information given in this technical sheet are in accordance to our best knowledge and can in no way be considered as an absolute guarantee on the final result which is linked to the specific working process of the customer.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA
Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repit - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

SCHEDA TECNICA TECHNICAL DATA SHEET

**PRODOTTO:
PRODUCT:**

129 - REPI COLOUR

Descrizione / Description

Dispersion of pigments in plasticizer

Funzione / Use

Colour for plastic materials.

Idoneo per / Suitable for

LDPE	ABS	PET	TR		UP
HDPE	PSA	PA	TPU	x	POM
PP	PSC	PMMA	PU ester	x	
PVC x	SAN	PC	PU ether	x	

Caratteristiche / Features

Metodo / Method

Aspetto Appearance	LIQUID	Visual
Colore Colour	GREEN	Visual
Viscosità a 20°C (cP) Viscosity at 20°C (cP)	2500	MO-LT-03(*)
Peso Specifico a 20°C (g/ml) Specific Gravity at 20°C (g/ml)	0,95	MO-LT-019(**)

(*) Brookfield RVF, disco N.4,20 giri minuto a 20°C, valore indicativo.
Brookfield RVF, spindle N.4,20 rpm at 20°C, indicative value.

(**) Valore indicativo.
Indicative value.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA

Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repil.it - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

PRODOTTO:**PRODUCT:****129 - REPI COLOUR****Indicazioni di impiego / General recommendations**

Use the product at the addition rate suggested by Repi.

Manipolazione e Stoccaggio / Handling and Storage

We recommend that you stir the product before using it. We suggest that the product be stored at room temperature. The viscosity of the product may greatly increase if it is stored at a low temperature. If this occurs, bring the product to room temperature and mix well prior to using it.

To avoid any humidity absorption and potential pollution, please store the product in a tightly sealed container.

Storage life: 6 months in sealed containers

Misure di sicurezza / Safety measures

Please refer to the information included on the material safety data sheet.

Redatta il/Completed on 1/06/98

Emissione nr/Issue nr 1

Repi S.p.A.
Via B. Franklin, 2
21050 LONATE CEPPINO (VA) - ITALY
Tel. +39 0331 819511 - Fax +39 0331 819581
E-mail repi@repil.it www.repi.it

REPI, LLC.
8700 Red Oak Boulevard, Suite D
Charlotte, North Carolina 28217
Tel. +1 704 5228841 - Fax +1 704 5228788
E-mail info@repil-usa.com www.repi-usa.com

All information given in this technical sheet are in accordance to our best knowledge and can in no way be considered as an absolute guarantee on the final result which is linked to the specific working process of the customer.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA
Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repit - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

SCHEDA TECNICA TECHNICAL DATA SHEET

**PRODOTTO:
PRODUCT:**

126 - REPI COLOUR

Descrizione / Description

Carbon black dispersion in plasticizer

Funzione / Use

Colour for plastic materials.

Idoneo per / Suitable for

LDPE	ABS	PET	TR		UP
HDPE	PSA	PA	TPU		POM
PP	PSC	PMMA	PU ester	x	
PVC	SAN	PC	PU ether	x	

Caratteristiche / Features

Metodo / Method

Aspetto Appearance	LIQUID	Visual
Colore Colour	BLACK	Visual
Viscosità a 20°C (cP) Viscosity at 20°C (cP)	1500	MO-LT-03(*)
Peso Specifico a 20°C (g/ml) Specific Gravity at 20°C (g/ml)	1,00	MO-LT-019(**)

(*) Brookfield RVF, disco N.4,20 giri minuto a 20°C, valore indicativo.
Brookfield RVF, spindle N.4,20 rpm at 20°C, indicative value.

(**) Valore indicativo.
Indicative value.

**REPI S.p.A.**

Sede Legale e Stabilimento: Via B. Franklin, 2 - 21050 Lonate Ceppino VA - ITALIA

Tel +39 0331 819511 - Fax +39 0331 819581 - repi@repil.it - www.repi.it

Capitale Sociale Euro 1.100.000,00 i.v.

Trib. Busto Arsizio n. 8934 - R.E.A. VA n. 127993 - M/VA024235

Cod. Fisc. e Reg. Imprese VA n. 00331580126 - Partita IVA / VAT number IT 00331580126

PRODOTTO:**PRODUCT:****126 - REPI COLOUR****Indicazioni di impiego / General recommendations**

Use the product at the addition rate suggested by Repi.

Manipolazione e Stoccaggio / Handling and Storage

We recommend that you stir the product before using it. We suggest that the product be stored at room temperature. The viscosity of the product may greatly increase if it is stored at a low temperature. If this occurs, bring the product to room temperature and mix well prior to using it.

To avoid any humidity absorption and potential pollution, please store the product in a tightly sealed container.

Storage life: 6 months in sealed containers

Misure di sicurezza / Safety measures

Please refer to the information included on the material safety data sheet.

Redatta il/Completed on 20/01/10

Emissione nr/Issue nr 1

Repi S.p.A.
Via B. Franklin, 2
21050 LONATE CEPPINO (VA) - ITALY
Tel. +39 0331 819511 - Fax +39 0331 819581
E-mail repi@repil.it www.repi.it

REPI, LLC.
8700 Red Oak Boulevard, Suite D
Charlotte, North Carolina 28217
Tel. +1 704 5228841 - Fax +1 704 5228788
E-mail info@repil-usa.com www.repi-usa.com

All information given in this technical sheet are in accordance to our best knowledge and can in no way be considered as an absolute guarantee on the final result which is linked to the specific working process of the customer.